# KELLY-MOORE\* PAINTS The Painter's Paint Store

# SAFETY DATA SHEET

## 1. Identification

Product identifier 5725 DTM Acrylic Primer/Finish

Other means of identification Non

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Kelly-Moore Paint Co., Inc.

Address 987 Commercial St., San Carlos, CA 94070

**Telephone** 1-800-874-4436

E-mail TAlvarez@kellymoore.com

Contact person Tiffany Alvarez

Emergency phone number CHEMTREC: 1-800-424-9300

## 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

**Hazard statement** Harmful to aquatic life with long lasting effects.

**Precautionary statement** 

Prevention Avoid release to the environment.

Response Wash hands after handling.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

## **Mixtures**

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	< 22
Zinc oxide	1314-13-2	< 2

All concentrations are in percent by weight (kg) unless ingredient is a gas. Gas concentrations are in percent by volume (I).

#### 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

5725 DTM Acrylic Primer/Finish SDS US

Most important symptoms/effects, acute and

delayed Indication of immediate

Treat symptomatically.

medical attention and special treatment needed

**General information** 

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Direct contact with eyes may cause temporary irritation.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment, Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Zinc oxide (CAS 1314-13-2)	PEL	5 mg/m3	Fume.
		5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. ACGIH Threshold Limit Values	•		
Components	Туре	Value	Form
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.

5725 DTM Acrylic Primer/Finish SDS US 929317 Version #: 01 Revision date: -2/6 Issue date: 30-July-2015

#### **US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Туре	Value	Form	
Zinc oxide (CAS 1314-13-2)	Ceiling	15 mg/m3	Dust.	
	STEL	10 mg/m3	Fume.	
	TWA	5 mg/m3	Dust.	
		5 mg/m3	Fume.	

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Use safety glasses, goggles, or face shield to protect eyes.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

## 9. Physical and chemical properties

**Appearance** Milky white to colored liquid.

Physical stateLiquid.FormLiquid.ColorVarious.

Odor Slightly ammoniacal.

Odor threshold Not available.

**pH** 7 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate < 1 (n-BuAc=1)

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Not available.

Flammability limit - upper

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density > 1 (Air=1)

Relative density Not available.

Solubility(ies)

Solubility (water) Moderately soluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

5725 DTM Acrylic Primer/Finish SDS US

**Viscosity** Not available.

Other information

**Explosive properties** Not explosive. Oxidizing properties Not oxidizing. VOC (Weight %) 90.68 g/l

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

#### Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. **Eve contact** Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

# Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Inhalation of titanium dioxide dust may cause cancer, however due to the physical form of the Carcinogenicity

product, inhalation of dust is not likely.

## IARC Monographs. Overall Evaluation of Carcinogenicity

Silicon dioxide, crystalline silica-free (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

# **NTP Report on Carcinogens**

# OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

**Further information** This product has no known adverse effect on human health.

5725 DTM Acrylic Primer/Finish SDS US

## 12. Ecological information

Ecotoxicity

Harmful to aquatic life with long lasting effects. The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a

harmful or damaging effect on the environment.

Components Species Test Results

Zinc oxide (CAS 1314-13-2)

Aquatic

Crustacea LC50 Water flea (Daphnia magna) 0.098 mg/l, 48 Hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

**Mobility in soil** This product is moderately water soluble and may disperse in soil.

Other adverse effects None known.

# 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

#### 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**Hazard categories** 

CERCLA Hazardous Substance List (40 CFR 302.4)

Zinc oxide (CAS 1314-13-2) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

5725 DTM Acrylic Primer/Finish

SDS US

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Zinc oxide	1314-13-2	< 2	

## Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### US state regulations

#### **US. Massachusetts RTK - Substance List**

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

Zinc oxide (CAS 1314-13-2)

#### US. New Jersey Worker and Community Right-to-Know Act

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

Zinc oxide (CAS 1314-13-2)

# US. Pennsylvania Worker and Community Right-to-Know Law

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

Zinc oxide (CAS 1314-13-2)

#### **US. Rhode Island RTK**

Zinc oxide (CAS 1314-13-2)

#### **US. California Proposition 65**

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

#### International Inventories

Country(s) or region Inventory name On inventory (yes/no)\* United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

30-July-2015 Issue date

**Revision date** Version # 01 Health: 1 **HMIS®** ratings

Flammability: 1 Physical hazard: 0

**Disclaimer** Kelly-Moore Paint Co., Inc. cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

5725 DTM Acrylic Primer/Finish SDS US

Issue date: 30-July-2015