

# Safety Data Sheet - Gorilla Wood Glue

Date Revised: 07/11/2014  
Date Issued: 07/11/2014

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (651) 603-3429

According to Regulation (EC) No. 453/2010

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name : Gorilla Wood Glue  
Synonyms : Polyvinyl Acetate Polymer product in water

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : Consumer Adhesives for building, carpentry, or hobby projects using any type of wood. It is water resistant (passes ANSI/HPVA Type II), sandable, and paintable.

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

Gorilla Glue Europe Limited  
CBTC, East Terrace, Euxton,  
Chorley PR7 6TE  
+44 (0) 843 507 1200

#### 1.4. Emergency telephone number

Emergency number : 1-651-603-3429 (Prosar)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Sens. 1 H317

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

R43

Full text of R-phrases: see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07


Signal word (CLP) : Warning  
Hazardous ingredients : Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone  
Hazard statements (CLP) : H317 - May cause an allergic skin reaction  
Precautionary statements (CLP) : P261 - Avoid breathing mist, spray, vapours.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

Other hazards not contributing to the classification : Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable



# Safety Data Sheet - Gorilla Wood Glue

Date Revised: 07/11/2014  
Date Issued: 07/11/2014

Version: 1.0


## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (651) 603-3429

According to Regulation (EC) No. 453/2010

### 3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
Water	(CAS No) 7732-18-5 (EC no) 231-791-2	49 - 52	Not classified
Vinyl acetate-Vinyl alcohol polymer	(CAS No) 25213-24-5 (EC no) 607-648-9	3 - 4	Xi; R36
2-Propanol, 1-phenoxy-	(CAS No) 770-35-4 (EC no) 212-222-7	1 - 1,5	Xi; R36
Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone	(CAS No) 55965-84-9 (EC no) 611-341-5 (EC index no) 613-167-00-5	0,002 - 0,004	T; R23/24/25 C; R34 R43 N; R50/53
3(2H)-Isothiazolone, 5-chloro-2-methyl-	(CAS No) 26172-55-4 (EC no) 247-500-7	0,0007 - 0,0015	T; R24/25 Xn; R20 C; R34 Xi; R41 R43 N; R50
Name	Product identifier	Specific concentration limits	
Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone	(CAS No) 55965-84-9 (EC no) 611-341-5 (EC index no) 613-167-00-5	(C >= 0,0015) R43 (0,06 =< C < 0,6) Xi;R36/38 (C >= 0,6) C;R34	
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Water	(CAS No) 7732-18-5 (EC no) 231-791-2	49 - 52	Not classified
Vinyl acetate-Vinyl alcohol polymer	(CAS No) 25213-24-5 (EC no) 607-648-9	3 - 4	Eye Irrit. 2, H319
2-Propanol, 1-phenoxy-	(CAS No) 770-35-4 (EC no) 212-222-7	1 - 1,5	Eye Irrit. 2, H319
Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone	(CAS No) 55965-84-9 (EC no) 611-341-5 (EC index no) 613-167-00-5	0,002 - 0,004	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3(2H)-Isothiazolone, 5-chloro-2-methyl-	(CAS No) 26172-55-4 (EC no) 247-500-7	0,0007 - 0,0015	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400
Name	Product identifier	Specific concentration limits	
Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone	(CAS No) 55965-84-9 (EC no) 611-341-5 (EC index no) 613-167-00-5	(C >= 0,0015) Skin Sens. 1, H317 (0,06 =< C < 0,6) Eye Irrit. 2, H319 (0,06 =< C < 0,6) Skin Irrit. 2, H315 (C >= 0,6) Skin Corr. 1B, H314	



# Safety Data Sheet - Gorilla Wood Glue

Date Revised: 07/11/2014  
Date Issued: 07/11/2014

Version: 1.0

**FOR CHEMICAL EMERGENCY:**  
During Business Hours: (800) 966-3458 | Outside Business Hours: (651) 603-3429

According to Regulation (EC) No. 453/2010

Full text of R- and H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).
- First-aid measures after inhalation : If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after eye contact : Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.
- First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause minor eye irritation. May cause mild skin irritation. Exposure may produce an allergic reaction.
- Symptoms/injuries after inhalation : None expected under normal conditions of use.
- Symptoms/injuries after skin contact : May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.
- Symptoms/injuries after eye contact : May cause eye irritation. Stinging, tearing, redness, and swelling of eyes.
- Symptoms/injuries after ingestion : Ingestion is likely to be harmful or have adverse effects.

### 4.3. Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : This product in solution form does not burn. The product will only burn after the water it contains is driven off. For the dry polymer, use alcohol resistant foam, carbon dioxide, or dry chemical.
- Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Explosion hazard : Product is not explosive.
- Reactivity : Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for firefighters

- Precautionary measures fire : Exercise caution when fighting any chemical fire.
- Firefighting instructions : Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures


- General measures : Do not get in eyes, on skin, or on clothing. Contaminated surfaces will become very slippery.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Use appropriate personal protection equipment (PPE).
- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.



# Safety Data Sheet - Gorilla Wood Glue

Date Revised: 07/11/2014  
Date Issued: 07/11/2014

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (651) 603-3429

According to Regulation (EC) No. 453/2010

## 6.2. Environmental precautions

Prevent entry to sewers and public waters.

## 6.3. Methods and material for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material, then place in suitable container.  
Methods for cleaning up : Clear up spills immediately and dispose of waste safely. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.

## 6.4. Reference to other sections

See Section 8 for Exposure Controls and Personal Protection. See Section 13 for Disposal Consideration.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Handling temperature : > 10 °C (50 °F)  
Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a dry, cool and well-ventilated place. Keep container closed when not in use.  
Incompatible products : Strong acids, strong bases, strong oxidizers, material that reacts with water.  
Maximum storage period : Varies depending on storage conditions. For best results, protect from frost and do not store in heat or direct sunlight. Keep tightly sealed and between temperatures 10 and 35°C (50 and 95°F).

### 7.3. Specific end use(s)

Consumer Adhesives for building, carpentry, or hobby projects using any type of wood. It is water resistant (passes ANSI/HPVA Type II), sandable, and paintable.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone (55965-84-9)

Austria	MAK (mg/m <sup>3</sup> )	0,05 mg/m <sup>3</sup>
---------	--------------------------	------------------------

#### 3(2H)-Isothiazolone, 5-chloro-2-methyl- (26172-55-4)

Austria	MAK (mg/m <sup>3</sup> )	0,05 mg/m <sup>3</sup>
---------	--------------------------	------------------------


### 8.2. Exposure controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal protective equipment : Protective clothing. Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection.



- Materials for protective clothing : Chemically resistant materials and fabrics.  
Hand protection : Wear chemically resistant protective gloves.  
Eye protection : Chemical safety goggles.  
Skin and body protection : Wear suitable protective clothing.  
Respiratory protection : If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.  
Other information : When using, do not eat, drink or smoke.



# Safety Data Sheet - Gorilla Wood Glue

Date Revised: 07/11/2014  
Date Issued: 07/11/2014

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (651) 603-3429

According to Regulation (EC) No. 453/2010

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Light Tan, Milky.
Colour	: No data available
Odour	: Sweet.
Odour threshold	: No data available
pH	: 2,5 - 3,5
Relative evaporation rate (butylacetate=1)	: No data available
Melting/Freezing point	: 0 °C (32 °F)
Boiling point	: 100 °C (212 °F)
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Viscosity	: 4000 - 6000 cP @ 25 °C (77 °F)
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizers, materials that react with water.

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>). Oxides of aluminum.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### 2-Propanol, 1-phenoxy- (770-35-4)


LD50 oral rat	2830 mg/kg
---------------	------------

LD50 dermal rat	> 2000
-----------------	--------

#### Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone (55965-84-9)

ATE CLP (oral)	100,000 mg/kg bodyweight
----------------	--------------------------

ATE CLP (dermal)	300,000 mg/kg bodyweight
------------------	--------------------------



## Safety Data Sheet - Gorilla Wood Glue

Date Revised: 07/11/2014  
Date Issued: 07/11/2014

Version: 1.0

**FOR CHEMICAL EMERGENCY:**  
During Business Hours: (800) 966-3458 | Outside Business Hours: (651) 603-3429

According to Regulation (EC) No. 453/2010

### Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-3(2H)-isothiazolone (55965-84-9)

ATE CLP (dust,mist)	0,500 mg/l/4h
---------------------	---------------

### 3(2H)-Isothiazolone, 5-chloro-2-methyl- (26172-55-4)

LD50 oral rat	481 mg/kg
LC50 inhalation rat (mg/l)	1,23 mg/l/4h
ATE CLP (oral)	100,000 mg/kg bodyweight
ATE CLP (dermal)	300,000 mg/kg bodyweight

Skin corrosion/irritation : Not classified  
pH: 2,5 - 3,5

Serious eye damage/irritation : Not classified  
pH: 2,5 - 3,5

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

#### 3(2H)-Isothiazolone, 5-chloro-2-methyl- (26172-55-4)

LC50 fishes 1	1,6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
EC50 Daphnia 1	4,71 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	0,12 - 0,3 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

#### 3(2H)-Isothiazolone, 5-chloro-2-methyl- (26172-55-4)

Log Pow	-0,71 - 0,75 (at 20 °C)
---------	-------------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

## SECTION 14: Transport information


In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

Not regulated for transport

### 14.2. UN proper shipping name

Not applicable



# Safety Data Sheet - Gorilla Wood Glue

Date Revised: 07/11/2014  
Date Issued: 07/11/2014

Version: 1.0

**FOR CHEMICAL EMERGENCY:**  
During Business Hours: (800) 966-3458 | Outside Business Hours: (651) 603-3429

According to Regulation (EC) No. 453/2010

## 14.3. Transport hazard class(es)

Not applicable

## 14.4. Packing group

Not applicable

## 14.5. Environmental hazards

Other information : No supplementary information available.

## 14.6. Special precautions for user

### 14.6.1. Overland transport

No additional information available

### 14.6.2. Transport by sea

No additional information available

### 14.6.3. Air transport

No additional information available

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	2-Propanol, 1-phenoxy-
--	------------------------

Contains no substance on the REACH candidate list

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out


## SECTION 16: Other information

Revision date : 07/11/2014

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

Full text of R-, H- and EUH-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage



## Safety Data Sheet - Gorilla Wood Glue

Date Revised: 07/11/2014  
Date Issued: 07/11/2014

Version: 1.0

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (651) 603-3429

According to Regulation (EC) No. 453/2010

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
R20	Harmful by inhalation
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed
R24/25	Toxic in contact with skin and if swallowed
R34	Causes burns
R36	Irritating to eyes
R36/37/38	Irritating to eyes, respiratory system and skin
R41	Risk of serious damage to eyes
R43	May cause sensitisation by skin contact
R50	Very toxic to aquatic organisms
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
C	Corrosive
N	Dangerous for the environment
T	Toxic
Xi	Irritant
Xn	Harmful

SDS EU (REACH Annex II)

*The information presented in this Safety Data Sheet was prepared by qualified personnel and to the best of our knowledge is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser will independently determine the suitability of the product for this purpose. This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which The Gorilla Glue Company assumes legal responsibility. The data is submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial and local laws and regulations.*