

S.C. Johnson Wax
 Racine, Wisconsin 53403-5011
 Phone: (414) 631-2777
 Emergency Phone: (800) 228-5635

4=Very High
 3=High
 2=Moderate
 1=Slight
 0=Insignificant

HAZARD RATING	
HMIS	NFPA
1 Health	
2 Flammability	
0 Reactivity	

MATERIAL SAFETY DATA SHEET

SECTION I-PRODUCT IDENTIFICATION

PRODUCT NAME: CONQ-R-DUST LIQUID		PRODUCT CODE 14760-4	
CHEMICAL OR COMMON NAME NA	DATE ISSUED: 04/17/91	SUPERSEDES: 02/11/91	PREPARED BY: Terry A. Meyers Chemical Info. Adm.

SECTION II-INGREDIENT INFORMATION

INGREDIENTS	WEIGHT %	EXPOSURE LIMIT
[NJ] Mineral Seal Oil (CAS# 64741-44-2)	75-90	5mg/m ³ (ACGIH TLV-TWA) (OSHA PEL)
Isoparaffinic Hydrocarbon Solvent (CAS# 64742-48-9)	5-10	300 PPM-EXXON RECOMMENDED
[PA,NJ,MA] Amyl Acetate (CAS# 628-63-7)	1-2	100 PPM ACGIH/OSHA TWA
See Regulatory Information (Section XII) for explanation of bracketed information.		

SECTION III-PHYSICAL DATA

APPEARANCE/ODOR: Clear slightly yellow with banana odor	SPECIFIC GRAVITY (H2O=1): 0.8
VAPOR PRESSURE (mm Hg): ND	PERCENT VOLATILE BY VOLUME (%): 100
SOLUBILITY IN WATER: Negligible	VAPOR DENSITY (Air=1): ND
FREEZING POINT (°F): ND	BOILING POINT (°F): ND
pH: NA	EVAPORATION RATE (Butyl Acetate=1): NA
VOC (as packaged, minus H2O): ND	THEORETICAL VOC (lb/gal): ND

SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT (°F) (Method Used): 101 (TCC)
FLAMMABLE LIMITS: ND
EXTINGUISHING MEDIA: Foam. CO2. Dry Chemical. Water Fog.
SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used. Cool and use caution when approaching or handling fire-exposed containers.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Liquid run-off to sewers may create fire/explosion hazard. Container may explode in heat of fire. Vapors may accumulate in confined spaces (e.g., pits, sumps, sewers) and inadequately ventilated areas.

SECTION V-HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: Skin contact.

MATERIAL SAFETY DATA SHEET

Page 2

S. C. Johnson Wax
1525 Howe Street
Racine, Wisconsin 53403

CONO-R-DUST LIQUID
Product Number: 14760
Serial Number: 4

SECTION V-HEALTH HAZARD DATA (cont.)

SIGNS AND SYMPTOMS: Prolonged or repeated contact of product with skin may cause irritation. Product may cause severe distress and serious illness if taken internally. If taken internally, aspiration of liquid product can cause chemical pneumonitis.

FIRST AID PROCEDURES: If product gets on skin, remove with soap and water. If product is swallowed, do not induce vomiting. Seek medical aid at once.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE: PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO IRRITATING EFFECTS.

SECTION VI-REACTIVITY DATA

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID: None known

INCOMPATIBILITY: None known

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID: None known

SECTION VII-BILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources. Do not let spilled or leaking material enter watercourse. Contains Amyl Acetate. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize.

WASTE DISPOSAL INFORMATION: Disposal is regulated under the Resource Conservation and Recovery Act as an ignitable waste (40 CFR 261.21). Disposal of regulated quantities should be by incineration at a permitted facility in accordance with all Federal/State regulations and local ordinances regarding disposal of ignitable wastes.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: No special requirements under normal use conditions.

VENTILATION: NSR

PROTECTIVE GLOVES: If prolonged or repeated contact is possible: Any impervious material.

Eye protection: No special requirements under normal use conditions.

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices. Launder contaminated clothing/equipment before reuse.

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONARY LABELING: DANGER: Harmful or fatal if swallowed. Contains mineral seal oil. If swallowed, do not force to throw up. Go to a doctor or hospital emergency room at once. Keep out of reach of children. CAUTION: Flammable mixture. Do not use near fire or flame.

MATERIAL SAFETY DATA SHEET

Page 3

S. C. Johnson Wax
1525 Howe Street
Racine, Wisconsin 53403

CONO-R-DUST LIQUID
Product Number: 14760
Serial Number: 4

SECTION IX-SPECIAL PRECAUTIONS (cont.)

OTHER HANDLING AND STORAGE CONDITIONS: Store in a cool, dry place with adequate ventilation. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Do not pressurize, cut, heat, weld or expose container to flame; explosion could occur.

SECTION X-ADDITIONAL INFORMATION

ADDITIONAL INFORMATION: NA

SECTION XI-TRANSPORTATION INFORMATION

DOT CLASS: Flammable liquid.

DOT #: NA1993.

SHIPPING NAME: Compound, cleaning, liquid, flammable liquid, NA 1993.

DOT NOTES: None

SECTION XII-REGULATORY INFORMATION

There are no ingredients subject to the reporting requirements under California's Proposition 65.

MA - These ingredients are subject to the reporting requirements under the Massachusetts Hazardous Substance List.

NJ - These ingredients are subject to the reporting requirements under the New Jersey Right to Know Hazardous Substance List.

PA - These ingredients are subject to the reporting requirements under the Pennsylvania Hazardous Substance List.

Not applicable, not established, NSR-No special requirement, not determined. The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use.